



XP-P442B

Mobile Receipt & Label Printer

Xprinter®

XP-P442B

Mobile Receipt & Label Printer



• Max. 4-inch label paper

50mm(1.9")



• 50mm(1.9") diameter paper roll




• Support direct USB charging



• Built-in paper bin,
adjustable paper width



• 2500mAh battery life
longer than other products



Printing	
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	102mm (4") / s
Max.print width	104 mm (4.09")
Max.print length	1016mm (40")
Media	
Media type	Continuous, gap, black mark
Media width	40 mm ~ 112 mm
Media thickness	0.06 mm ~0.16 mm
Label roll diameter	50mm (1.96")
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	USB+Bluetooth (Optional: NFC, WIFI, Bluetooth)
Screen	OLED (1.3")
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code, MPDF417, AZTEC, MAXICODE
Rotation	0°、 90°、 180°、 270°
Emulaion	TSPL, EPL, ZPL, DPL, CPCL, ESC/POS
Physical Features	
Dimensions	150×131×64mm (D×W×H)
Weight	583 g
Reliability	
Printer head life	30Km
Software	
Operation system	Windows / Android / iOS
SDK	Windows / Android / iOS
Power supply	
Power input	Input: AC 100-240V, 0.5A 50-60Hz; Output: DC 5V/2A
Battery	7.4V / 2500mAh
Environmental Conditions	
Operation environment	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity: 10 ~ 90% no condensing



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

