

# BTP-M300

# POS

Impact printer

[www.orient-technologies.com](http://www.orient-technologies.com)



# NEW!

#### Applications:

Retail  
Hospitality  
Vending  
Ticketing  
Logistics  
Coupon  
Lottery

#### Standard features at a glance:

- Bi-directional print
- Two-color print
- Support continuous paper and marked paper
- Varis paper width range
- Paper saving features
- Support various interfaces
- Support big volume buzzer
- Internal power supply



**ORIENT Technologies** by  
a subsidiary of SNBC of Weihai/China **SNBC**



Kitchen



Restaurants



Bar



Drugstore



Shopping Mall



Cosmetic Shop



Convenience Store

**ORIENT Technologies** b.v.

Meerheide 115, 5521 DX Eersel, The Netherlands  
Phone +31 (0)497 331080, Fax +31 (0)497 386430

# BTP-M300

## POS impact printer

<b>Print</b>	
Print Method	9-pin serial impact dot matrix
Print width	Max. 400(half dots)/200(full dots)
Columns	40(7x9)/33(9x9); 42(7x9)/35(9x9);
Print speed	≥ 4.7LPS (400 dots/line).
Drivers	Windows driver (Win2000/XP, WinServer2003/2008, VISTA, Win7, Win8);
Interface	A. USB+CDKO or Ethernet+CDKOB. Attachable interfaces (daughter board): 1) RS232 2) Centronics 3) USB 4) Ethernet 5) WLAN (Wi-Fi)
Cash drawer control	1-2 cash drawers
Fonts	Font A: 9x9 Font B: 7x9 Kanji: 16x16
Characters/inch	Font A: 13.3CPI, Font B: 16CPI, Kanji: 8.9CPI
Character modification	Rotate(0°,90°,180°,270°), enlarges(1-6X), emphasize, underline, reverse

### Data Buffer

Receive buffer	8K
NV bit image data area	128K
User NV memory	1K

### Paper

Paper type	Continuous paper, Marked paper
Single layer thickness	0.06~0.085mm
Multi-layer thickness (1 original+1 copies)	0.05-0.08mm, total thickness≤0.14 mm
Paper width	80±0.5mm,76±0.5mm,69.5±0.5mm,57.5±0.5mm
Paper roll OD	83mm (Max.)
Paper cut	Full cut, Partial cut, Tear off

### Ribbon

Ribbon specification	ERC-38
Ribbon lifetime	ERC-38(P): 4 million characters ERC-38(B): 3 million characters ERC-38(B/R)Black: 1.5 million characters ERC-38(B/R)Red: 0.75 million characters

### Power supply

Input/Output	100~240 VAC, 50~60 Hz/ 24±5%V DC, 1.5A
--------------	--

### Reliability

Printer head lifetime	10,000,000 lines
Printer mechanism lifetime	150,000,000 lines
Cutter lifetime	1,800,000 cuts (standard test condition)

### Environment

Operating conditions	5°C to 45°C, 20% to 90%RH (40°C)
Storage conditions	-40°C to 60°C, 20% to 93%RH (40°C)

### Physics Spec.

Dimensions	160 (W) X 245 (D) X 154 (H) mm
Weight	Approx. 3.2 kg

### Certification

CE, CB, UL, FCC, RoHS, EnergyStar



**ORIENT Technologies bv**  
Meerheide 115, 5521 DX Eersel, The Netherlands  
Phone: +31 (0)497 331080, Fax: +31 (0)497 386430  
[www.orient-technologies.com](http://www.orient-technologies.com)

The specifications are subject to change without notice and shall not be regarded as a warranty. All product and company names are trademarks, service marks or registered trademarks of their respective owners.