



1D



2D



DPM



IP64



USB



**NVF260**  
Stationary Scanners

## Features

### DPM Decoding.

With a new generation of industrial decoding, the NVF260 is excellent at reading DPM barcodes even on curved surfaces.

### Advanced Illumination.

The NVF260's blue illumination ring helps to reduce bottlenecks in the scanning process by avoiding the reflection from materials with metal surfaces.

### Impressive Image Sensor.

With a 1280x800 megapixel imager, the NVF260 can decode up to 3-millimetre barcodes.

### Industrial Design.

Built with an IP64 housing, the NVF260 easily resists water and dust. The medical-grade housing is also able to be sterilized without alcohol damage.

## Suggested industries



Healthcare



Industrial



Manufacturing

# NVF260 Technical specifications

## Performance

Image Sensor	1280x800 CMOS
Illumination	Diffuse: ring of blue LED
Depth of Field Data Matrix (10mil)	0-25mm
Depth of Field QR (15mil)	0-30mm
Minimal Print Contrast	50%
Scan Angle Roll	360°
Scan Angle Pitch	±40°
Scan Angle Skew	±40°
Field of View Horizontal	32.7°
Field of View Vertical	20.7°

## Data Capture

1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Code 128, Code 39, Codabar, UCC/EAN 128, AIM128, Interleaved 2 of 5, ITF-14, ITF-6, Standard 2 of 5, Matrix 2 of 5, COOP 25, Industrial 2 of 5, Plessey, MSI Plessey, Code 11, Code 93, ISBT128, Deutsche 14, Deutsche12
2D	QR Code, Data Matrix

## Physical

Dimensions (mm)	Height: 100mm, Diameter: 65mm
Weight	347g
Interfaces	USB TYPE-C
Notifications	Beep, LED indicator
Input Voltage	5VDC±5%
Current @ 5VDC Operating	230mA (typical), 330mA (max)
Power Consumption	1150mW (typical)

## Environmental

Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	20°C to 70°C (-4°F to 158°F)
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±8 KV (direct discharge); ±15 KV (air discharge)
Drop	1.2m
IP Rating	IP64

## Certifications

Hardware	FCC Part15 Class B, CE EMC Class B
----------	------------------------------------

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved