

1D & 2D



5G







Android

Laser Megapixel

10"

screen













Touchscreen USB-C

9000 mAh

SD







WIFI Dual Band

Bluetooth

NFC**)** NFC

الان **GPRS**







coating



Antibacterial





Supports.

1D and 2D barcodes.

Software.

Built on Android 11 GMS (AER).

Touch screen.

10.0 inch (1920 x 1200) 5 point capacitive touch screen.

Processor.

Octa-core 2.2 GHz CPU.

Memory.

4GB RAM and 64GB Flash memory.

Offers.

WiFi 802.11 a/b/g/n/ac (2.4GHz & 5GHz), Bluetooth 5.1, GPS, camera, NFC, GSM, WCDMA.

(SPEEDATA

SD100MD

Orion Plus

Speedata

Accessories.

Support hand strap for ease of use. Optional charging cradle and vehicle cradle.

Suggested industries



Hospitality



Healthcare



Public Sector





SD100MD Orion Plus Technical specifications

ь.	.4-	0-	-4		
Da	пи	100	ш	ure	3

1D All major 1D symbologies

2D All major 2D symbologies

Performance

Operating System Android 11 GMS (AER)

Processor Octa-core 2.2 GHz

4GB Memory RAM

Memory Flash 64GB

Physical

Audio Front dual stereo speakers, Volume 90db±3db (test distance 10cm)

Audio Jack 3.5mm earphone jack

Battery Type 9000mAh

Rear 13MP AF, high brightness LED flash, front 5MP camera Camera

Dimensions (mm) 254 x 176 x 17.4 mm

Display 10" (1200x1920) IPS highlight screen

Expansion Slot 2 Micro SIM card slots, 1 SD card slot

Expected Battery Life Typical working time not less than 10 hours

Expected Charge Time fast charging, full charging time<4 hours

Interfaces USB Type-C

Keypad 12 buttons

Notifications Sound, vibration, LED

20 Pogo Pins contact Pogo Pin

Sensors Gsensor, Ambient light sensor, Proximity sensor

Touch Panel 5-point capacitive touch screen

Weight 800g (with battery)

Wireless

WWAN RADIO FDD-LTE B1/B3/B5/B7/B8, TDD-LTE B38/B39/B40/B41, TDSCDMA B34/B39, WCDMA B1/B2/B5/B8, GSM

B2/B3/B5/B8, CDMA 1 x/CDMA2000 BC0/BC1

WLAN RADIO IEEE 802.11 a/b/g/n/ac 2.4G 5G dual frequency

WPAN RADIO Bluetooth 5.1 BLE

RFID ISO14443A/B, ISO15693, NFC Reading distance: 0~5cm; UHF ISO18000-6C, Euro frequency (865MHz -

867MHz), Antenna: 1.5dBi ceramic antenna, Power: 5dBm~30dBm adjustable, 1dbm step, Working range:

Indoor >12m, Outdoor >6m, Inventory speed: >200 tags/sec

GPS GPS+BD+GLONASS

Environmental

-20°C to 55°C **Operating Temperature**

-30°C to 70°C Storage Temperature

Humidity 5%-95%

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

Feel free to contact us or a partner near you



SD100MD Orion Plus Technical specifications

Electro Static Discharge (ESD)	± 15kV air discharge , ±8kV contact discharge
Drop	1 meter drop to concrete
IP Rating	IP65
Certifications	
Hardware	CCC, CE
Warranty	
Standard	2 years



Feel free to contact us or a partner near you