

# Xprinter®

## Thermal Receipt Printer

### XP-S200M/S260M/S300M

- New sleek shell design
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind
- Screen can be added (XP-S300M)



# XP-S200M/S260M/S300M

## Thermal Receipt Printer



Printing	XP-S200M	XP-S260M	XP-S300M
Printing method	Direct thermal		
Paper width	57.5±0.5mm / 79.5±0.5mm		
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm		
Column capacity	576 dots/line(adjustable by command)		
Printing speed	200 mm/s	260 mm/s	300 mm/s
Interface	USB+Serial/USB+Lan (Optional: Bluetooth/WIFI)	USB+ Serial+Lan (Optional: Bluetooth/WIFI)	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)		
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns		
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)		
<b>Cutter</b>			
Auto cutter	Partial		
<b>Barcode Character</b>			
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)		
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QR CODE / PDF417 (Unavailable in interfaces: USB+Serial /USB+WiFi/USB+Bluetooth)		
Input buffer	128 Kbytes	128 Kbytes	2048 Kbytes
NVFlash	256 Kbytes	256 Kbytes	256 Kbytes
<b>Power</b>			
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A		
Printer input	DC 24V/2.5A		
Cash drawer	DC 24V/1A		
<b>Physical characteristics</b>			
Weight	0.97 Kg		
Dimensions	180×140×134.1mm (D×W×H)		
<b>Environmental Requirements</b>			
Operation environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)		
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)		
<b>Reliability</b>			
Cutter life	1.5 million cuts		
Printer head life	150 KM		
<b>Software</b>			
Emulation	ESC/POS		
Driver	Windows/JPOS/ OPOS/Linux/Android/Mac		
Utility	Windows & Linux test Utility		
SDK	iOS/Android/Windows		



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

